

SURVEY DATASHEET (Version 1.0)

PID: BBCC12
Designation: BRG286-046
Stamping: DIMPLE
Stability: Most reliable; expected to hold position well
Setting: Abutment or pier of large bridges
Description: From the intersection of County Road 272 and County Road 286 on the south end of Seminole Island, heading Southwesterly with the centerline of County Road 286 a distance of 1555' +/- and West 13' +/- to a dimpled 2" dia. Brass domed disk set in the West end of the South abutment of Bridge 286-0.46.
Observed: 2010-10-05T12:56:00Z
Source: OPUS - page5 1009.28



Close-up View

REF_FRAME: NAD_83(CORS96)	EPOCH: 2002.0000	SOURCE: NAVD88 (Computed using GEOID09)	UNITS: m	SET PROFILE	DETAILS
-------------------------------------	----------------------------	--	--------------------	--------------------	----------------

<p>LAT: 40° 29' 26.91380" ± 0.038 m LON: -83° 52' 29.31954" ± 0.005 m ELL HT: 271.500 ± 0.040 m X: 518322.894 ± 0.003 m Y: -4829972.310 ± 0.030 m Z: 4119760.085 ± 0.042 m ORTHO HT: 305.572 ± 0.071 m</p>	<p>UTM 17 SPC 3401(OH N) NORTHING: 4486205.321m 92436.985m EASTING: 256356.718m 483450.498m CONVERGENCE: -1.86760668° -0.90318250° POINT SCALE: 1.00033076 0.99998949 COMBINED FACTOR: 1.00028816 0.99994690</p>
---	---

CONTRIBUTED BY

[gdappert](#)
 Logan County Engineers Office



Horizon View



The numerical values for this position solution have satisfied the quality control criteria of the National Geodetic Survey. The contributor has verified that the information submitted is accurate and complete.